

**WHEELED FIRE EXTINGUISHERS**

Series 4500

**DRY CHEMICAL:**

Carts and framing components are made of rugged steel. All brass cylinder valve and hose valve assemblies are chrome plated. Hoses are quick release and non-kinking.

**CARBON DIOXIDE:**

Spun steel cylinder-brass chrome plated valves. Designed for one person operation. Reinforced wire braided hose. Pneumatic tires 16" X 4".

**REGULAR DRY CHEMICAL:**

Carts and framing components are made of rugged steel. All brass cylinder valve and hose valve are chrome plated. Quick release non-kinking hoses.

**HALOTRON:**

Cylinders with chrome plated brass valve. Equipped with all weather semi-pneumatic 16" diameter 4" wide tires for easy moveability.



Figure No. 4510



Figure No. 4580



Figure No. 4530

All Types and Sizes of Wheeled extinguishers are available upon request.

Figure No.	Type	Use	U/L Rating	Capacity	Discharge time (sec)	Discharge Range	Hose Length	Height	Dimensions Width	Depth	Shipping Weight
4510	Dry Chemical ABC		30A-160B:C	50	35	25-35	25'	47	21.5	24.6	174 Lbs.
4520	Dry Chemical ABC		40A-240B:C	125	48	30-40	50'	50 1/2	28.7	40.1	344 Lbs.
4530	CO2		20 B:C	50	44	15	15'	60	48	23.5	257lbs.
4535	CO2		20 B:C	100	74	15	40'	65	30	21	461 Lbs.
4570	Regular Dry Chemical		240BC	150	48	30-40	50'	50	28.7	40.1	369 Lbs.
4580	Halotron		4A-40BC	65	22	30-45	50'	58	28.7	41.5	300 Lbs.
4590	Halotron		10A-80BC	150	38	30-45	50'	64	30.7	41.5	480 Lbs.