



Figure No. 5130

CAP SOLD SEPARATELY

GATE VALVES 200LB. & 300LB. RATED


Straightway Pattern hose gate valves are intended for use on standpipes, fire pump test connections and hydrants.

FEMALE X MALE

STANDARD EQUIPMENT: Female NPT inlet x Male hose thread outlet, cast brass with wheel handle, solid wedge disc with tapered seats.

NOTE:

- Figure No. 5110 - 1 1/2 X 1 1/2 - non-rising stem
- Figure No. 5115 - 2 1/2 X 2 1/2 - rising stem
- Figure No. 5120 - 3 X 2 1/2 - rising stem
- Figure No. 5130 - 2 1/2 X 2 1/2 - non-rising stem



**SPECIFY
THREAD**

OPTIONAL FINISHES:

- PB - Polished Brass
- RC - Rough Chrome Plated
- PC - Polished Chrome Plated

*

Figure No.	Size Male X Female	U/L Listed	Max. PSI	A	B Closed	C	D Closed	D Open
5110	1 1/2 x 1 1/2	No	200	3 1/2	5	1 1/2	6 1/2	7 1/4
5115	2 1/2 x 2 1/2	No	200	6 1/2	11	2 1/2	13 1/2	16 1/4
5120	3 x 2 1/2	Yes	300	6 13/16	11	2 1/2	13 1/2	16 1/4
5130	2 1/2 x 2 1/2	Yes	300	6 1/2	10 3/4	2 1/2	13 1/4	13 1/4

NOT RECOMMENDED FOR WET SYSTEMS



Figure No. 5135

CAP SOLD SEPARATELY

GATE VALVES 300LB. RATED


Straightway Pattern, non-rising stem, 300lb. PSI.. Hose gate valves are intended for use on standpipes, fire pump test connections and hydrants

FEMALE X MALE

STANDARD EQUIPMENT: Female NPT inlet x male hose thread outlet, cast brass with wheel handle, solid wedge disc with tapered seats.

NOTE:

- Figure No. 5135- 2 1/2 X 2 1/2 - non-rising stem
- Figure No. 5140- 3 X 2 1/2 - non-rising stem



**SPECIFY
THREAD**

- OPTIONAL FINISHES:**
- PB - Polished Brass
 - RC - Rough Chrome Plated
 - PC - Polished Chrome Plated
- U/L LISTED**

Figure No.	Size Female X Male	A	B	C	D
5135	2 1/2 X 2 1/2	4 11/32	7 13/32	11 57/64	9 19/64
5140	3 x 2 1/2	4 17/32	7 13/32	11 57/64	9 19/64

NOT RECOMMENDED FOR WET SYSTEMS